

Ans B1
Ans B2

Ans B1

The present invention relates to a knee prosthesis and more specifically to the device for assembling its tibia plate, which is made of plastic, on its metal base anchored beforehand into the tibia bone tissue.

5

Knee prostheses which comprise a plastic tibia part which is free to rotate about the tibia bone axis with respect to the metal base secured to the tibia are known.

10

This freedom of rotation is generally achieved via a male shaft integral with the plastic tibia part which engages with a bore made in the metal base.

15

Furthermore, this freedom of rotation may be achieved by a male shaft secured to the metal base which engages with a bore made in the plastic tibia part.

20

These connecting devices have certain drawbacks, namely the difficulty of inserting the plastic tibia plate once the metal base is in place on the tibia. These drawbacks are exacerbated when the posterior cruciate ligament is being kept, as this restricts access to the upper part of the tibia.

25

Furthermore, it is observed that the center of rotation is necessarily positioned at a point of the device or [sic] the bore can be made, that is to say in a part or [sic] there is enough material to make the said bore.

30

This arrangement of the center of rotation is not strictly anatomical.

35

It can be seen that the volume generated by the tibia bone axis may prevent a posterior cutout from being made in the plastic tibia plate or in the metal base to allow the posterior cruciate ligament to be kept.

Ans B2

Knee prostheses which comprise a plastic tibia plate which slides freely over the flat surface of the metal

09832374-044201
FOI 200-4232360

base, and the movement of which is limited by one or more cylindrical studs integral with the base communicating with spaces made in the said plastic plate are also known.

5

This type of prosthesis has the drawback of not physically embodying an axis of rotation.

It is these drawbacks which the present invention sets
10 out more particularly to overcome.

Ans B57
The knee prosthesis according to the present invention is intended to provide a plastic tibia plate which has a degree of freedom in rotation with respect to the
15 metal base.

Ans B57
The knee prosthesis in accordance with the present invention comprises a metal base and a tibia plate which are equipped with guide means defining a center
20 of rotation which may be offset from that of the tibia bone axis, so as to allow the tibia plate to slide in rotation over the said base, the said guide means being positioned a certain distance away from the center of rotation.

Ans B57
The knee prosthesis has guide means which consist of at least one upstand in the shape of an arc of a circle secured to the metal base and of a housing with the same radius of curvature made in the plastic tibia
25 plate to allow the latter to slide in rotation about the center of rotation of the said upstand.
30

Ans B57
The knee prosthesis according to the present invention comprises guide means which consist of an upstand in
35 the shape of an arc of a circle, which upstand is positioned in the anterior part of the metal base and oriented in a substantially medio-lateral direction.

09832874-041201

5

the
com

10
the
inv

20

25 The
com

30
The
com

The knee prosthesis according to the present invention comprises a metal base which has two upstands in the shape of an arc of a circle, of constant height and

SECRET

5 The knee prosthesis according to the present invention comprises upstands which are set out opposite one another, and have one and the same center of rotation.

10 The knee prosthesis according to the present invention comprises a metal base which has, opposite the upstand, a retaining peg borne by a center of rotation so as to engage with a cutout formed in the tibia plate to prevent the latter from lifting off the base as the said plate slides in rotation about its center of rotation.

~~100372 The knee prosthesis according to the present invention comprises a retaining peg which consists of a cylindrical pin integral with a head which has a larger diameter than the said pin so that the said head engages with inclined faces made in the cutout.~~

25 The knee prosthesis according to the present invention comprises a metal base which has, opposite the upstand, a centering peg borne by the center of rotation so as to engage with a blind hole formed in the tibia plate to guide the latter with respect to the base as the said plate slides in rotation about its center of rotation.

30 The knee prosthesis according to the present invention comprises a metal base and a tibia plate which respectively comprise a cutout through which the posterior cruciate ligament can pass.

35 ~~the knee prosthesis according to the present invention comprises a metal base which has two upstands in the shape of an arc of a circle curved in the same direction and centered about the same center, of~~

rotation, while the tibia plate comprises housings intended to receive the said upstands respectively, so as to allow the said plate to slide in rotation about the center of rotation.

5

Aug 17

The knee prosthesis according to the present invention comprises an upstand which is integral with a flange which engages in a slot in the housing to prevent the tibia plate from lifting off the metal base as the said plate slides in rotation about the center of rotation.

15

Aug 17

The knee prosthesis according to the present invention comprises a metal base which comprises two upstands in the shape of an arc of a circle in opposite directions and centered about the same center of rotation, while the tibia plate comprises an element and a housing which are intended to receive the said upstands respectively to allow the said plate to slide in rotation about the center of rotation.

20

The knee prosthesis according to the present invention comprises an upstand which is set out on the external periphery of the horizontal disk of the metal base so as to engage with a peripheral recess in the tibia plate.

25

Aug 17

The knee prosthesis according to the present invention comprises an upstand which is offset from the center of rotation and comprises a flange which snap-fastens into the housing in the tibia plate to, on the one hand, guide the plate as it slides in rotation about its center and, on the other hand, retain the said plate so that it does not lift off the metal base.

30

Aug 17

The knee prosthesis according to the present invention comprises a metal base which comprises a peripheral upstand in the shape of an arc of a circle integral with a flange directed toward the tibia bone vertical axis and a housing set out in the region of the center

09832374.04204

of rotation, while the tibia plate has, on its external periphery, a recess in which there is formed a horizontal slot intended to receive the flange of the said upstand and, on its lower face, a stub which
5 engages with the housing.

Ans B23
The knee prosthesis according to the present invention comprises a metal base which comprises three peripheral upstands extending vertically above the horizontal
10 disk, while the tibia plate has, on its external periphery, three recesses intended to receive the said upstands respectively to allow the said plate to be guided as it slides in rotation about the center of rotation.

Ans B21
15 The knee prosthesis according to the present invention comprises pegs which are set out in an arc of a circle about a center of rotation, while the tibia plate has a housing intended to receive the said pegs.

Ans B22
20 The knee prosthesis according to the present invention comprises pegs which have a center of rotation which is borne by the tibia bone vertical axis, while the said peg is a certain distance away from its center of
25 rotation.

Ans B23
The knee prosthesis according to the present invention comprises pegs which have a center of rotation which is offset from the tibia bone vertical axis, while the
30 said peg is a certain distance away from its center of rotation.

Ans B24
The knee prosthesis according to the present invention comprises a metal base which comprises at least one
35 upstand or peg which engages with a housing of the tibia plate so that the said plate can slide in rotation over the metal base only within the limit set by the difference in size between the said upstand or peg and the said corresponding housing.

09832874-041201
T02T40-422E860

The knee prosthesis according to the present invention has a rotational travel between the tibia plate and the metal base which is reduced to zero when the dimensions
5 of the housing are made so as to engage without clearance with the upstand.

Ans B25

The knee prosthesis according to the present invention has a short height of the guide means and of their
10 anterior positioning on the metal base which allows the tibia plate to be mounted on the said base via a strictly anterior approach, the said plate requiring upward clearance only by the height of the said guide means.

15

Ans B25

The description which will follow with reference to the appended drawings, given by way of nonlimiting examples, will allow a good understanding of the invention, its features and the advantages it is likely
20 to afford.

Figure 1 is an exploded perspective view illustrating the knee prosthesis according to the present invention.

25 Figures 2 and 3 are side views showing the knee prosthesis before the plastic tibia plate is fitted on the metal base.

Figures 4 and 5 are views depicting a first alternative
30 form of the knee prosthesis according to the invention.

B

Figures 6, 7 and 8 are views illustrating a second alternative form of the knee prosthesis in which the metal base has two opposed guide upstands.

35

Ans B27

Figures 9, 10 and 11 are views showing a third alternative form of the knee prosthesis in which the metal base has, on its axis of rotation, a peg for retaining the plastic tibia plate.

09837274-041201

Ans B 27
Figures 12, 13 and 14 are views showing a fourth alternative form of the knee prosthesis in which the metal base has, on its axis of rotation, an additional 5 peg for centering the plastic tibia plate.

Ans B 27
Figures 15, 16 and 17 are views depicting a fifth alternative form of the knee prosthesis which has a cutout through which the posterior cruciate ligament 10 can pass.

Ans B 27
Figures 18 to 24 are views illustrating alternative forms of the knee prosthesis in which the metal base has two opposed guide upstands but one of which is 15 borne by the center of rotation of the second.

Ans B 27
Figures 25 to 27 are views depicting other alternative forms of the knee prosthesis according to the present invention.

20
Ans B 32
Figures 28 and 29 are views illustrating guide means set out at the periphery of the metal base and of the tibia plate of the knee prosthesis.

Ans B 32
Figures 30 to 32 are views showing guide means consisting of at least two vertical pegs integral with the metal base and which engage with a housing formed in the tibia plate.

Ans B 31
Figures 1 to 3 show a knee prosthesis 1 comprising a metal base 2 and a tibia plate 3, whereas the femoral element is not depicted.

Ans B 31
The metal base 2 consists of a horizontal disk 20 35 secured on one of its faces to an anchoring rod 21 allowing the said base to be fixed into the tibia of a patient.

09832874-041204

5 C of the upstand 22 is borne by the tibia bone vertical axis YY'.

410837

15 distance away from the center of rotation C.

Anders

On the opposite side to the face 30 the tibia plate 3 has an upper face 31 with two tracks 32 and 33 of concave profile which are intended to receive the condyles of the femoral element, not depicted.

The lower face 30 is pierced with a housing 34 with the same radius of curvature as the upstand 22 secured to the metal plate 2.

which are intended to receive respectively the central part 23 and the lateral edges 24 and 25 of the upstand 22.

particularly its lower face 30, is resting on the horizontal disk 20 of the metal base 2, that the upstand 22 enters the housing 34.

[illegible]

~~ANSWER~~
The latter has dimensions that exceed those of the upstand 22 so that the tibia plate 3 can slide freely in rotation about the center of rotation C of the said upstand 22 in the direction of the arrow F illustrated in Figure 1.

The upstand 22, which is in the shape of an arc of a circle or curved, is positioned in the anterior part of the metal base 2 and oriented in a substantially medio-lateral direction.

Figures 4 and 5 show a first alternative form of the knee prosthesis 1 according to the present invention.

15 The knee prosthesis 1 is identical to the one described earlier, that is to say that it comprises a metal base 2 and a plastic tibia plate 3.

~~ANSWER~~
20 The metal base 2 has, and this is what differentiates it from the one described above, the position of the guide means on the horizontal disk 20. In effect, the guide means consist of an upstand 22 in the shape of an arc of a circle and the profile of which is similar to the one described earlier, but the center of rotation 25 C' of which is offset from that C borne by the tibia bone vertical axis YY'.

~~ANSWER~~
30 Note that the center of rotation C' can be positioned anywhere, either on the horizontal disk 20 or off it, while at the same time keeping the guide means on the said horizontal disk and more specifically at a particular point.

Just as before, the upstand 22 provided with its 35 central part 23 and its lateral edges 24 and 25 enters the housing 34 formed in the lower face 30 of the plastic tibia plate 3 to allow the latter to slide in rotation over the metal base 2 and about the center of

09832874-041201

rotation C' in the direction of the arrow F1 in Figure 4.

5 The upstand 22, which is in the shape of an arc of a circle or curved, is positioned in the anterior part of the metal base 2 and oriented in a substantially medio-lateral direction.

B

10 Figures 6 to 8 depict a second alternative form of the knee prosthesis 1 according to the invention.

The latter comprises a metal base 2 and a plastic plate 3 similar to those described in Figure 1, but in which the guide means differ to allow for a better movement
15 of the plate over the base.

Thus, the metal base 2 equipped with its horizontal disk 20 integral with its rod 21 comprises guide means which consist of two opposed upstands 22' and 22'' in
20 the shape of an arc of a circle. The upstands 22' and 22'' have the same center of curvature which is coincident with the center of rotation C located on the tibia bone vertical axis YY'.

25 Provision may be made for the center of rotation of the upstands 22' and 22'' to differ from the one C, that is to say offset as shown in the first alternative form in Figures 4 and 5.

30 Note too that the upstands 22' and 22'' have a constant height over the entire circular-arc-shaped profile.

The tibia plate 3 has a flat lower face 30 with two opposed housings 34' and 34'' intended to receive
35 respectively the upstands 22' and 22'' of the metal base 2. The housings 34' and 34'' have a radius of curvature identical to that of the upstands 22' and 22''.

109832374-041201

B

It can be seen when the tibia plate 3, and more specifically its lower face 30, is resting on the horizontal disk 20 of the metal base 2, that the upstands 22' and 22'' enter the housings 34' and 34''.

5

The latter have dimensions greater than those of the upstands 22' and 22'' so that the tibia plate 3 can slide freely in rotation about the center of rotation C in the direction of the arrow F3 illustrated in Figure

10 6.

~~FIG 10~~ Figures 9 to 11 illustrate a third alternative form of the knee prosthesis 1 according to the present invention.

15

The knee prosthesis 1 is identical to the one described in Figures 1 to 3, namely it comprises a metal base 2 and a plastic tibia plate 3.

~~FIG 11~~ The metal base 2 comprises, on its horizontal disk 20, and on the opposite side to its anchoring rod 21, guide means which consist of the upstand 22 formed from a central part 23 and of two lateral edges 24 and 25.

25 Furthermore, the horizontal disk 20 comprises, at the center of rotation C of the upstand 22 which is borne by the tibia bone vertical axis YY', a retaining peg 26 extending vertically above the said disk 20.

30 The retaining peg 26 constitutes a guide means that is in addition to the guide means formed by the upstand 22. Thus, the peg 26 is positioned on the center of rotation C of the tibia plate 3 on the metal base 2.

~~FIG 12~~ The retaining peg 26 consists of a cylindrical pin 27 integral with a head 28 whose outside diameter exceeds that of the said pin.

09832274-041201

The additional guide means or peg 26 is an integral part of the pin 27, 28 to prevent the tibia plate 3 from lifting off the metal base 2 when the prosthesis is in motion.

The tibia plate 3 has, on its lower face 30, the housing 34 that receives the upstand 22 and a cutout 35 with inclined faces 36. When the plate 3 is mounted on the base 2, this cutout engages with the retaining peg 26 so that the head 28 lies above the inclined faces 36.

0679 It can be seen that the retaining peg 26, when it engages with the cutout 35, allows the tibia plate 3 to be prevented from lifting under a tensile force when the said plate is sliding in rotation F4 on the metal base 2.

~~Figures 12 to 14 show a fourth alternative form of the~~
~~knee prosthesis 1 according to the invention.~~

Thus, the metal base 2 comprises, opposite the upstand 22, and in the region of the center of rotation C which is borne by the tibia bone vertical axis YY', a centering peg 29 extending vertically above the horizontal disk 20.

25 ~~The centering peg 29 extends vertically above the~~
~~horizontal disk 20 by a short height, constituting a~~
30 ~~guide means that is in addition to the guide means~~
~~formed by the upstand 22.~~

The centering peg 29 consists of a short cylindrical pin.

35
NOB 7 The plastic tibia plate 3 comprises, on its lower face 30 and opposite the housing 34, a blind hole 37 intended to receive the centering peg 29 when the said plate is fitted onto the metal base 2.

The centering peg 29 provides a physical embodiment of the center of rotation C of the upstand 22 as the tibia plate 3 slides in rotation over the metal base 2.

5
~~Ans B51~~ The knee prosthesis 1 illustrated in Figures 15 to 17 differs from the one shown in Figures 1 to 3 only in the fact that the metal base 2 and the plastic tibia plate 3 respectively comprise a cutout 4 and 38 for the
10 passage of the posterior cruciate ligament.

~~Ans B51~~ Quite obviously, the prosthesis 1 shown in Figures 15 to 17 works in the same way as the one described in Figures 1 to 3.

15
~~Ans B51~~ Figure 18 shows the knee prosthesis 1 equipped with its metal base 2 and with its tibia plate 3. The metal base 2 comprises, on its horizontal disk 20, and more specifically on the opposite side to the anchoring rod
20 21, an upstand 5 in the shape of an arc of a circle and of variable height. This upstand has a profile which differs from those that make up the upstands described earlier. At the center of rotation C of the upstand 5 there is a second upstand 6 in the shape of an arc of a
25 circle.

~~Ans B51~~ The upstands 5 and 6 engage in housings, not depicted, but formed on the face 30 of the tibia plate 3 to allow the said plate to be guided as it slides in rotation
30 about the center of rotation C, as depicted by the arrow F5.

The upstand 5, in the shape of an arc of a circle or curved, is positioned in the anterior part of the metal
35 base 2 and oriented in a substantially medio-lateral direction.

~~Ans B51~~ The upstand 6 constitutes a guide means that is in addition to the guide means formed by the upstand 5.

09032874.041201

Provision may be made for the center of rotation of the upstands 5 and 6 to be offset from the tibia bone vertical axis YY' without this in any way altering the subject of the invention.

Ans 557

The housing 7 has a profile essentially identical to that of the upstand 5, and at the very least, in the shape of an arc of a circle for guiding the tibia plate 25 3 in its travel.

1000

Ans B57

Note that the upstands 5 and 6 in the shape of an arc of a circle are curved in the same direction and about

the same center of rotation C or C' when the latter is offset from the tibia bone vertical axis YY'.

Ans 1358

As in Figure 15, the metal base 2 and the tibia plate 3 may respectively comprise cutouts 4 and 38 for the passage of the posterior cruciate ligament.

Ans 1359

In Figures 22 to 24 the knee prosthesis 1 comprises, on its metal base 2, a first upstand 5' set out at the external periphery of the horizontal disk 20. Opposite the upstand 5' the horizontal disk 20 is secured to another upstand 9 in the shape of an arc of a circle, but the radius of curvature of which is inverted compared with that of the upstand 5'.

15

The upstand 5, which is in the shape of an arc of a circle or curved, is positioned in the anterior part of the metal base 2 and oriented in a substantially medio-lateral direction.

Ans 1360

20 The upstand 9 constitutes a guide means that is in addition to the guide means formed by the upstand 5'. Thus, the upstand 9 is positioned on the center of rotation C of the tibia plate 3 on the metal base 2.

Ans 1361

25 The upstand 9 has the same center of rotation C as the upstand 5', but the said center may be offset, depending on the configuration of the knee prosthesis, from the tibia bone vertical axis YY'.

30

The upstand 9 is integral with a flange 90, the function of which will be seen more clearly later.

The tibia plate 3 has, on its lower periphery, that is to say the one that lies between the faces 30 and 31, a recess 10 receiving the upstand 5' when the tibia plate 3 is fitted onto the metal base 2.

35

090322874-041201

Ans B42

On the opposite side to the recess 10, the lower face 30 is pierced with a housing 12 into which the upstand 9 can be snap-fastened to, on the one hand, guide the plate 3 as it slides in rotation about its center C, and, on the other hand, retain the said plate to prevent it from lifting off the metal base 2.

Ans B43

In Figures 25 to 27 the knee prosthesis 1 comprises the metal base 2, the horizontal disk 20 of which has, on its external periphery, an upstand 13 in the shape of an arc of a circle integral with a flange 14 directed toward the tibia bone vertical axis YY'.

Ans B44

The horizontal disk 20 is pierced at the center of rotation C of the upstand 13 with a dish-shaped housing 15 which constitutes a guide means that is in addition to the guide means formed by the said upstand 13. This upstand, which is in the shape of an arc of a circle or curved, is positioned in the anterior part of the metal base 2 and oriented in a substantially medio-lateral direction.

The upstand 13 and the housing 15 may comprise a center of rotation C which is offset from the tibia bone vertical axis YY'.

On its external periphery and between the faces 30 and 31, the tibia plate 3 has a recess 10' in which there is formed a horizontal slot 16 intended to receive the flange 14 of the upstand 13 as the plate 3 slides in rotation over the metal base 2.

The lower face 30 is integral with a stub 17 with a conical tapering profile capable of engaging with the housing 15 formed in the horizontal disk 20 of the metal base 2.

Ans B45

The upstand 13 equipped with its flange 14, the housing 15, the recess 10' and its slot 16, and the stub 17

09032374.041204

in Figures 28 and 29, the metal base 2 of the knee prosthesis 1 comprises, on its horizontal disk 20, three peripheral upstands 50, 51 and 52 extending vertically above the said horizontal disk 20.

15 The tibia plate 3 comprises, on its external periphery, three peripheral recesses 53, 54 and 55 which are intended to receive the upstands 50, 51 and 52 respectively to allow the said plate to be guided as it slides in rotation about the center of rotation of the said upstands, which is identical for all three.

The upstand 51, which is the shape of an arc of a circle or curved, is positioned in the anterior part of the metal base 2 and oriented in a substantially medio-lateral direction.

25 The upstands 50, 52 in the shape of an arc of a circle constitute guide means which are in addition to the guide means formed by the upstand 51. The upstands 50, 52 are positioned near the center of rotation C of the tibia plate 3 on the metal base 2.

~~In figures 30 to 32, the metal base 2 of the knee prosthesis 1 comprises, on its horizontal disk 20, vertical pegs 18 set out in an arc of a circle about a center of rotation C which may be either borne by or offset from the tibia bone vertical axis YY'.~~

35 The pegs 18 set out in an arc of a circle are positioned in the anterior part of the metal base 2 and oriented in a substantially medio-lateral direction.

~~In this example, the tibia plate 3 is identical to the one described in Figures 1 to 3, that is to say that~~

~~its lower face 30 has a housing 34 intended to receive the pegs 18 for guiding the said plate as it slides in rotation with respect to the metal base 2.~~

5 It can be seen that in each example described
hereinabove it is possible, as the case may be, for the
center of rotation of the upstands or of the pegs
either to be offset or not to be offset in order to
determine a particular rotational sliding of the tibia
10 plate 3 with respect to the metal base 2.

Note too that in each example described hereinabove, cutouts 4 and 38 may or may not be provided for the passage of the posterior cruciate ligament.

15 Furthermore, it can be seen that the guide means in
each example described hereinabove are positioned a
certain distance away from the center of rotation C,
C'.

20
b7c
it will be observed that the short height of the
upstand or of the pegs, and its anterior position on
the metal base 2 allows the plastic plate 3 to be
fitted onto the said base easily using a strictly
25 anterior approach, the plate requiring upward clearance
only by the height of the said upstand or of the said
pegs as shown in Figure 21.

It will furthermore be observed that the plastic plate 30 3 cannot slide in rotation over the metal base 2 except within the limits set by the difference in dimensions between the housing and the corresponding upstand or peg, and this prevents any undesired excess movement.

~~01137 This being so, it will be readily understood that a plastic plate 3 can be obtained in which the dimensions of the housing are identical to those of the upstand or of the corresponding pegs, so as to prevent any travel of the said plate over the metal base 2. This allows~~

the surgeon, according to the particular surgical case, to return to a knee prosthesis system with plastic plate which is fixed to the metal base 2, without having to change the latter.

09032874-041201